

REPLACEMENT PARTS GUIDE

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)



Required Parts

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Description	Image	PartNumber	Quantity	Interval Hrs	Remarks
1	Engine Oil Filter		MIU800650	1	500	
2	Final Fuel Filter		MIU805005	1	500	
3	Primary Fuel Filter Element		MIU802421	1	500	
4	Hydraulic Oil Reservoir Breather		AT101565	1	500	
5	500 Hour Filter Pak for Compact Construction		AT535106	1	500	Includes AT101565, MIU800650, MIU802421 and MIU805005
6	Hydraulic Oil Filter		AT495722	1	1000	
7	Hydraulic Oil Filter		AT314164	1	1000	Hydrostatic Oil Filter
8	Fuel Tank Vent Filter		H216169	1	1000	Fuel Tank Breather
9	1000 Hour Filter Pak		AT535111	1	1000	Includes AT314164, (2) H216169, AT101565, KV16429, AT171854, MIU800650, MIU802421, MIU805005 and AT495722



Required Parts




330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Description	Image	PartNumber	Quantity	Interval Hrs	Remarks
10	Engine Rocker Arm Cover Gasket		MIU802567	1	1500	
11	DEF Header Inlet Filter Kit		AT502963	1	2000	Diesel Exhaust Fluid Header Suction Filter and Baffle
12	Diesel Exhaust Fluid (DEF) Injection Pump Filter Kit		DZ114640	1	2000	Diesel Exhaust Fluid Dosing Unit
13	Fuel Tank Vent Filter		H216169	1	4000	For Diesel Exhaust Filter
14	Cab Fresh Air Filter		AT441536	1	AR	
15	Cab Air Filter		AT359416	1	AR	Recirculation Air Filter
16	Primary Air Filter Element		KV16429	1	AR	
17	Secondary Air Filter Element		AT171854	1	AR	
18	Diesel Particulate Filter		MIU804396	1	AR	



Required Parts

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Description	Image	PartNumber	Quantity	Interval Hrs	Remarks
19	Engine Fan Drive V-Belt, Effective Length 1800 mm (71 inch)		T428862	1	AR	With Air Conditioning
20	Engine Pulley V-Belt, Effective Length 1565 mm (61.6 inch)		T428858	1	AR	Without Air Conditioning
21	Dust Unloader Valve		R48568	1	AR	



Oil & Capacities

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Description	Qty or Capacity	Interval Hrs	Remarks
1	John Deere Plus-50™ II Engine Oil	12.0 L (3.0 gal)	500	
2	John Deere Hydrostatic Motor Gear Case Oil (per side)	0.8 L (27.0 fl oz)	500	
3	John Deere Hydrau Hydraulic Oil	34.0 L (9.0 gal)	1000	
4	John Deere Hy-Gard Chain Case Oil	44 L (11.6 gal)	1000	
5	John Deere Cool-Gard™ II Premix	10 L (2.5 gal)	6000	

Plus-50 is a trademark of Deere & Company.

Hydrau is a trademark of Deere & Company

Hy-Gard is a trademark of Deere & Company

Cool-Gard is a trademark of Deere & Company.



Fluid Analysis Test Kits

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Description	Part Number	Qty or Capacity	Interval Hrs	Remarks
1	Universal Fluid Analysis Kit	AT346594	1	250	Engine Oil
2	Universal Fluid Analysis Kit	AT346594	1	500	Hydraulic Oil
3	Engine Coolant Kit with Oil Detection	TY27788	1	500	Engine Coolant

See operator's manual for recommended oil type and oil viscosities based on operating temperatures.

Based on fluid analysis results, intervals may need to be adjusted for operating conditions. Consult an authorized John Deere dealer.



Service Instructions

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Service Hrs	Instructions
1	50	Check and clean dust unloader valve
2	50	Lubricate Quik - Tatch Engagement Pins
3	250	Take engine oil sample
4	500	Change Engine Oil
5	500	Replace Engine Oil Filter
6	500	Replace primary fuel filter
7	500	Replace final fuel filter
8	500	Check chain case oil level
9	500	Replace hydraulic reservoir breather
10	500	Take engine coolant sample
11	500	Take hydraulic oil sample
12	500	Change hydrostatic motor gear case oil
13	1000	Change hydraulic oil
14	1000	Replace hydraulic oil filter
15	1000	Replace hydrostatic oil filter
16	1000	Replace fuel tank breather
17	1000	Change chain case oil
18	1000	Check engine coolant condition
19	1500	Check and adjust engine valve lash
20	2000	Replace diesel exhaust fluid (DEF) dosing unit filter
21	2000	Replace diesel exhaust fluid (DEF) header suction filter
22	2000	Replace diesel exhaust fluid (DEF) Baffle
23	2000	Clean diesel exhaust fluid (DEF) tank



Service Instructions

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Service Hrs	Instructions
24	4000	Replace diesel exhaust fluid (DEF) tank breather filter
25	6000	Drain and refill cooling system
26	AR	Check accessory drive belt
27	AR	Check cab fresh air filter
28	AR	Check cab recirculation air filter
29	AR	Check and clean cooling package
30	AR	Replace primary engine air filter element
31	AR	Replace secondary engine air filter element (with every third primary filter or as needed)
32	AR	Drain water and sediment from fuel tank
33	AR	Check and drain primary fuel filter and water separator according to water in fuel indicator.
34	AR	Service exhaust filter
35	AR	Check and adjust steering mistracking
36	AR	Check Tire Pressure
37	AR	Check wheel fastners
38	AR	Clean and tighten battery terminals
39	AR	Clean camera lens (if equipped)
40	Daily	Check Level of engine coolant
41	Daily	Check Level of engine oil
42	Daily	Check level of hydraulic oil
43	Daily	Lubricate boom linkage
44	Daily	Lubricate cylinder pivot points



Service Instructions

330G Skid Steer Loader (PIN: 1T0330G__F387881- 468047)

Sequence	Service Hrs	Instructions
45	Daily	Lubricate Quik - Tatch Linkage ¹
46	Daily	Lubricate anti vibration bogie pivot

¹Quik-Tatch is a trademark of Deere & Company

