



*JOHN DEERE 750 SERIES GRAIN DRILL
(MANUFACTURED 1989-1998)*



NP4250

*JOHN DEERE 750 SERIES GRAIN DRILL
(MANUFACTURED 1990-)*

(SPECIFICATIONS AND DESIGN ARE SUBJECT TO CHANGE WITHOUT NOTICE.)

SERIAL NUMBERS

WHEN WRITING OR FILLING OUT WARRANTY CLAIMS, USE ALL NUMBERS, LETTERS AND SPACES SHOWN ON THE SERIAL NUMBER PLATE

MAIN FRAME SERIAL NUMBER PLATE IS ILLUSTRATED AS DESIGNATED

N00750X016550

N0 - DESIGNATES FACTORY
0750 - DESIGNATES INTEGRAL GRAIN DRILL MODEL
X - FOR DRILLS
016550 - DESIGNATES DRILL SPECIFIC NUMBER

SPECIFIC SERIAL NUMBERS BY MODEL YEAR ARE AS FOLLOWS:

1990 - 1994 - N/A
1995 - 016550
1996 - 019190
1997 - 023198
1998 - 025152

DIRECTION ARROW

ARROWS ARE USED WITH ILLUSTRATIONS TO INDICATE THE FRONT OF THE UNIT. "RIGHT-HAND" AND "LEFT-HAND" SIDES ARE DETERMINED BY FACING IN THE DIRECTION OF MACHINE FORWARD TRAVEL.

BOX-ENCLOSED ILLUSTRATIONS

A KEY NUMBER, SHOWN IN THE PARTS LIST, IS ASSIGNED TO A BOX ENCLOSING ALL PARTS SOLD AS A SERVICE ASSEMBLY.

BOLT AND CAP SCREW STRENGTH IDENTIFICATION

BOLTS AND CAP SCREWS REQUIRED TO HAVE HIGH-STRENGTH QUALITIES EQUIVALENT TO SAE GRADE 8 ARE IDENTIFIED THROUGHOUT THIS CATALOG BY THE DESCRIPTION HS SAE 8. ALL STANDARD BOLTS AND CAP SCREWS ARE SAE GRADE 5 OR LOWER.

COMPLETE GOODS LISTINGS

COMPLETE GOODS ARE LISTED IN BOLD FACE TYPE. ORDER SEPARATELY. DO NOT INCLUDE ON REPLACEMENT PARTS ORDER.

SI UNITS OF MEASURE

METRIC DIMENSIONS ARE GIVEN, WHERE APPLICABLE, THROUGHOUT THIS PARTS CATALOG.

HOSE DIMENSIONS LISTED ARE EITHER FITTING SIZE X LENGTH X FITTING SIZE OR I.D. X LENGTH.